



Rotary Valves

- Feeding and mining of pulverulent and granular products
- Range of machines that can process capacities from 5 to 450 m³/h
- Driving geared motor and elastic coupler
- Standard and high vacuum execution
- Special concept allowing the passage of large gradings

Rotary Valves

Flange dimension

Type	L mm	w mm	H mm	Input - mm		Output - mm		Capacity m ³ /h	Motor kW	Δp Allowed mbar	Mesh Size mm
				L	w	L	w				



Rotary valves (standard and high vacuum)

Pulverulent product

10 L	675	494	356	232	256	232	256	9	0.55	50	40
10 HV	675	599	356	232	256	232	256	9	1.1	500	40
16 L	680	599	356	361	256	361	256	14	1.1	50	40
16 HV	680	718	356	361	256	361	256	14	1.1	500	40
45 L	811	877	500	569	288	569	288	40	2.2	50	40
45 HV	811	998	500	569	288	569	288	40	2.2	500	40



Rotary valves

Pulverulent and granular product

045 -Z	1,920	510	544	500	185	650	205	40	1.5	120	40
048 -Z	2,120	510	544	800	185	950	205	65	1.5	120	40
0410 -Z	2,420	510	544	1,000	185	1,150	205	80	1.5	120	40
056 -Z	2,070	675	655	600	220	750	250	75	2.2	120	50
058 -Z	2,265	675	655	800	220	950	250	100	2.2	120	50
0510 -Z	2,465	675	655	1,000	220	1,150	250	125	3	120	50
066 -Z	2,080	780	880	600	290	750	320	110	2.2	120	60
068 -Z	2,320	780	880	800	290	950	320	150	3	120	60
0610 -Z	2,560	780	880	1,000	290	1,150	320	190	3	120	60
086 -Z	2,710	990	1,094	620	395	760	425	200	5.5	120	80
088 -Z	2,910	990	1,094	820	395	960	425	265	5.5	120	80
0810 -Z	3,110	990	1,094	1,020	395	1,160	425	330	5.5	120	80



Rotary valves with mobile screen

Pulverulent and granular product that can contain big pieces

044 -ZS	1,985	840	710	400	240	560	350	30	1.5	-	100
045 -ZS	2,085	840	710	500	240	660	350	40	1.5	-	100
048 -ZS	2,231	840	710	820	240	960	650	65	1.5	-	100
056 -ZS	2,044	790	684	600	219	750	249	75	2.2	-	100
058 -ZS	2,405	940	810	800	340	960	400	100	3	-	100
0510 -ZS	2,566	940	810	1,000	340	1,160	400	125	3	-	100
066 -ZS	2,175	1,062	1,015	600	417	770	670	110	4	-	200
068 -ZS	2,375	1,062	1,015	800	417	970	670	150	4	-	200
0610 -ZS	2,575	1,062	1,015	1,000	417	1,170	670	190	4	-	200
086 -ZS	2,710	1,262	1,215	600	567	770	820	200	5.5	-	300
088 -ZS	2,910	1,262	1,215	800	567	970	820	265	5.5	-	300
0810 -ZS	3,110	1,262	1,215	1,000	567	1,170	820	330	5.5	-	300
0815 -ZS	3,370	1,262	1,215	1,500	567	1,660	820	450	7.5	-	300

Besides his line of rotary valves has KH Mineral also a wide range of pendulum flap gates witch can be used in many fields.

ThyssenKrupp KH Mineral SAS

Parc Industriel Sud - ZI Neuwald

1, rue René François Jolly

B.P. 70537

F-57205 Sarreguemines

Tél. (33) 03 87 98 73 73 - Fax (33) 03 87 98 89 18 ou (33) 03 87 95 40 73

Email : contact@khmineral.com

Internet : www.khmineral.com